



# WALL BRACKET

## BSQ100 (4FT) SERIES (2' AVAILABLE)

SQUARE WALL BRACKET LUMINAIRE



DATE	
JOB	


WWW.LALIGHTING.COM  
626-454-8300

### APPLICATIONS


COMMERCIAL



### DIMENSIONS



- ◆ 11/16 K.O.
- ⊕ 7/8" OFFSET K.O.
- ⊕ 2" K.O.



### SPECIFICATIONS

#### FEATURES

- Wall mounted LED luminaire
- Provides front light and down light
- 0-10V dimming driver standard (other dimming types available)
- Controls and sensors available
- Wireless control options (Lutron, EnOcean, ZigBee, etc.)
- Supports California Title 24 compliance
- Suitable for damp locations
- Additional lumen packages and color temperatures available
- Full customization available upon request

#### CONSTRUCTION

- 22 ga. cold rolled steel welded housing
- 45-degree mounting bracket available
- Switch available

#### OPTICAL

- Clear prismatic acrylic lens
- Variety of lenses available

#### ELECTRICAL

- High efficiency drivers coupled with long-life LEDs
- Service life greater than 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Emergency battery pack available

#### FINISH

- Baked white powder coated finish
- Minimum reflectance 90%
- Painted after fabrication
- Custom colors available

### CUSTOM COLORS

BLK - Matte Black

CS - Camaro Silver

BZ - Statuary Bronze

Variety of RAL colors & Axalta/DuPont colors available upon request.

### CERTIFICATIONS



### ORDERING INFORMATION

EXAMPLE: BSQ100-2-4L-PA-BPL-1DRDM-UNV-1/840

SERIES	LED LUMEN PACKAGE	NOMINAL LENGTH	OPTICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROW	CRI / CCT
<b>BSQ100</b>		<b>4L</b>				<b>UNV</b>	<b>1</b>	
<b>BSQ100</b> Square Wall Bracket LED Luminaire	2 Nom. 2000 Lumens 4 Nom. 4000 Lumens 6 Nom. 6000 Lumens 8 Nom. 8000 Lumens <i>*Additional Lumen Packages Available</i>	<b>4L</b> 4'	<b>PA</b> Clear Prismatic Acrylic  <b>FPA</b> Frosted Prismatic Acrylic	<b>BPL</b> Emergency Battery Pack  <i>*Leave Blank if Not Specified</i> <i>Additional Electrical Options</i>	<b>1DRDM</b> 0-10V One Dimming Driver  <i>Additional Driver Options</i>	<b>UNV</b> 120V-277V  <i>*Additional Voltages Available</i>	<b>1</b> One LED Row	<b>835</b> 80+CRI / 3500K Color Temp.  <b>840</b> 80+CRI / 4000K Color Temp.  <b>850</b> 80+CRI / 5000K Color Temp.  <i>*Additional Color Temp. Available</i>



Los Angeles Lighting Mfg. Co.

Headquarters  
10141 Olney Street  
El Monte, CA 91731  
Made in the USA

Contact Us  
T: 626-454-8300  
F: 626-454-8399  
www.lalighting.com

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

Revised 04-04-18

## SYSTEM DATA

NOMINAL SIZE	LED LUMEN PACKAGE	OPTICAL	CRI / CCT	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	FLUORESCENT / HID EQUIVALENT	IES FILES
4'	2000 lm	PA	840	1734 lm	16.6 W	104.5 lm/W	1-F32T8	<a href="#">LA-T2947</a>
	4000 lm	PA		3448.6 lm	33.3 W	103.6 lm/W	2-F32T8, 1-F54T5HO	<a href="#">LA-T2938</a>
	6000 lm	PA		4909 lm	55.2 W	89.0 lm/W	3-F32T8	<a href="#">LA-T2939</a>
	8000 lm	PA		6576 lm	68.6 W	95.9 lm/W	4-F32T8, 2-F54T5HO, 175 W (MH)	<a href="#">LA-T2940</a>

**NOTE:**

System data above is based on 120V input voltage.

Actual performance may differ as a result of end-user environment and application.

This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range from -20°C to 35°C.


Additional lumen packages and color temperatures available.

## ACCESSORIES

**45MB**

- 45-Degree Mounting Bracket
- Designed for mounting lighting fixtures at 45° angle
- Ideal for wall or ceiling mount applications
- 18 ga. electro galvanized steel
- Baked white powder coated finish

Note: Must drill own holes for 45-Degree Mounting Bracket.

**CEILING MOUNT****WALL MOUNT****Los Angeles Lighting Mfg. Co.**

Headquarters  
10141 Olney Street  
El Monte, CA 91731  
Made in the USA

Contact Us  
T: 626-454-8300  
F: 626-454-8399  
www.lalighting.com

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

Revised 04-04-18