



RESOURCES OPTICAL OPTIONS

Please consult factory regarding any optical options not shown.
Not all optics suitable for all fixtures. Please consult factory to ensure selected optical option suits selected fixture.

EXTRUDED PRISMATIC PATTERNS

*Normal stock item

FPA2	Frosted Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
PA*	Clear Prismatic Acrylic, No Thickness Specified, Female Prisms 3/16 Square Base
PA2*	Clear Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
PA3	Clear Prismatic Acrylic, Min. 0.125 OA Thickness, Female Prisms 3/16 Square Base
PA8*	Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base
P15	Clear Prismatic Acrylic, Nom. 0.200 OA Thickness, Female Prisms 3/8 Square Base
P195	Clear Prismatic Acrylic, Nom. 0.150 OA Thickness, Male Conical Prisms 3/16 Square Base
P198	Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Male Conical Prisms 3/16 Square Base
PWA2	White Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
P3E	3E Batwing Pattern Lens
P195RF	Clear Prismatic Acrylic, 19 Shunts Radio Frequencies To Ground, Nom. 0.150 OA Thickness
PA2UV	Clear Prismatic Acrylic, UV Blocking, Nom. 0.125 OA Thickness

FLAT DIFFUSERS

*Normal stock item

FWA*	Flat White Acrylic, No Thickness Specified, Stippled Finish	FWA2	Flat White Acrylic, Nom. 0.125 Thickness, Stippled Finish
FFA	Frosted Flat Acrylic, No Thickness Specified	FFA2	Frosted Flat Acrylic, Nom. 0.125 Thickness
CA*	Clear Acrylic, No Thickness Specified	CA2*	Clear Acrylic, Nom. 0.125 OA Thickness
CA8	Clear Acrylic, Nom. 0.187 OA Thickness		

HIGH IMPACT

*Normal stock item

VL25	Clear Polycarbonate, Nom. 0.125 Thickness with 0.125 Clear Prismatic Acrylic Overlay
VL37	Clear Polycarbonate, Nom. 0.250 Thickness with 0.125 Clear Prismatic Acrylic Overlay
CPC2	Clear Polycarbonate, Nom. 0.125 OA Thickness
CPC8	Clear Polycarbonate, Nom. 0.187 OA Thickness
PPC2	Clear Prismatic Polycarbonate, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
PPC8	Clear Prismatic Polycarbonate, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base
DRP2*	High Impact Clear Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
DRP3	High Impact Clear Prismatic Acrylic, Min. 0.125 OA Thickness, Female Prisms 3/16 Square Base
DRP8*	High Impact Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base

DROP PANS

DP	Dropped Opal Acrylic Dish, Stippled Finish, 1_1/2" Standard Drop
-----------	--

LOUVERS

P1S	Paracube Silver Finish, 1/2" x 1/2" x 7/16" Parabolic Cells	PLA	Eggcrate White Acrylic Louver, 1/2" x 1/2" x 3/8", 30° Cutoff
P2S	Paracube Silver Finish, 1 1/2" x 1 1/2" x 1" Parabolic Cells	ALW	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Baked White Enamel Finish
P3S	Paracube Silver Finish, 3" x 3" x 1 1/2" Parabolic Cells	ALB	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Baked Black Enamel Finish
P4S	Paracube Silver Finish, 3/4" x 3/4" x 1/2" Parabolic Cells	ALN	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Natural Anodized Finish



Los Angeles Lighting Mfg. Co.

Headquarters
10141 Olney Street
El Monte, CA 91731
Made in the USA

Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.