



# RESOURCES

## OPTICAL OPTIONS

Please consult factory regarding any optical options not shown

### EXTRUDED PRISMATIC PATTERNS

\*Normal stock item

<b>FPA2</b>	Frosted Prismatic Acrylic, Nom. 0.125 OA Thickness
<b>PA*</b>	Clear Prismatic Acrylic, No Thickness Specified, Female Prisms 3/16 Square Base
<b>PA2*</b>	Clear Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>PA3</b>	Clear Prismatic Acrylic, Min. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>PA8*</b>	Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base
<b>P15</b>	Clear Prismatic Acrylic, Nom. 0.200 OA Thickness, Female Prisms 3/8 Square Base
<b>P195</b>	Clear Prismatic Acrylic, Nom. 0.150 OA Thickness, Male Conical Prisms 3/16 Square Base
<b>P198</b>	Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Male Conical Prisms 3/16 Square Base
<b>PWA2</b>	White Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>P3E</b>	3E Batwing Pattern Lens
<b>P195RF</b>	Clear Prismatic Acrylic, 19 Shunts Radio Frequencies To Ground, Nom. 0.150 OA Thickness
<b>PA2UV</b>	Clear Prismatic Acrylic, UV Blocking, Nom. 0.125 OA Thickness

### FLAT DIFFUSERS

\*Normal stock item

<b>FWA*</b>	Flat White Acrylic, No Thickness Specified, Stippled Finish	<b>FWA2</b>	Flat White Acrylic, Nom. 0.125 Thickness, Stippled Finish
<b>FFA</b>	Frosted Flat Acrylic, No Thickness Specified	<b>FFA2</b>	Frosted Flat Acrylic, Nom. 0.125 Thickness
<b>CA*</b>	Clear Acrylic, No Thickness Specified	<b>CA2*</b>	Clear Acrylic, Nom. 0.125 OA Thickness
<b>CA8</b>	Clear Acrylic, Nom. 0.187 OA Thickness		

### HIGH IMPACT

\*Normal stock item

<b>VL25</b>	Clear Polycarbonate, Nom. 0.125 Thickness with 0.125 Clear Prismatic Acrylic Overlay
<b>VL37</b>	Clear Polycarbonate, Nom. 0.250 Thickness with 0.125 Clear Prismatic Acrylic Overlay
<b>CPC2</b>	Clear Polycarbonate, Nom. 0.125 OA Thickness
<b>CPC8</b>	Clear Polycarbonate, Nom. 0.187 OA Thickness
<b>PPC2</b>	Clear Prismatic Polycarbonate, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>PPC8</b>	Clear Prismatic Polycarbonate, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base
<b>DRP2*</b>	High Impact Clear Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>DRP3</b>	High Impact Clear Prismatic Acrylic, Min. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>DRP8*</b>	High Impact Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base

### DROP PANS

<b>DP</b>	Dropped Opal Acrylic Dish, Stippled Finish, 1_1/2" Standard Drop
-----------	--

### LOUVERS

<b>P1S</b>	Paracube Silver Finish, 1/2" x 1/2" x 7/16" Parabolic Cells	<b>PLA</b>	Eggcrate White Acrylic Louver, 1/2" x 1/2" x 3/8", 30° Cutoff
<b>P2S</b>	Paracube Silver Finish, 1 1/2" x 1 1/2" x 1" Parabolic Cells	<b>ALW</b>	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Baked White Enamel Finish
<b>P3S</b>	Paracube Silver Finish, 3" x 3" x 1 1/2" Parabolic Cells	<b>ALB</b>	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Baked Black Enamel Finish
<b>P4S</b>	Paracube Silver Finish, 3/4" x 3/4" x 1/2" Parabolic Cells	<b>ALN</b>	Eggcrate Aluminum Louver, 1/2" x 1/2" x 1/2", Natural Anodized Finish



#### Los Angeles Lighting Mfg. Co.

Headquarters  
10141 Olney Street  
El Monte, CA 91731  
Made in the USA

Contact Us  
T: 626-454-8300  
F: 626-454-8399  
www.lalighting.com

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.