




# CLEANROOM GCR210

CLASS 100 CLEANROOM GRID LUMINAIRE

JOB	
TYPE	
DATE	


## Grid-Mounted




COMPATIBLE T-BAR GRIDS	
WIDTH	HEIGHT
15/16"	1 1/2"
1 1/2"	1 1/2"



## CROSS SECTION



## BACKPLATE



\* No Unused Holes or KOs on Backplates

## SPECIFICATIONS

### Construction

- Class 100 / ISO Class 5 equivalent
- 22 gauge cold-rolled steel welded housing
- All parts fitted and sealed, no unused holes or knockouts
- 20 gauge cold-rolled steel door frame secured by full length piano hinge and 2 captive screws
- Door frame and lens sealed with closed cell neoprene gasket

### Finish

- Painted after fabrication
- Baked white powder-coated finish
- Minimum reflectance 90%

### Optical

- Inverted clear prismatic acrylic lens (nominal 0.125" thickness)

### Electrical

- High efficiency drivers coupled with long-life LEDs
- Service life greater than 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF)  $\geq 0.9$
- Total Harmonic Distortion (THD)  $\leq 20\%$

### Listing

- UL USA and Canada listed / suitable for damp locations

### Warranty

- 5-Year limited warranty standard. 10-Year limited warranty also available

## APPLICATIONS

- Cleanroom, Sealed Ceiling Areas, Commercial

## FEATURES

- 0-10V dimming driver standard
- Supports California Title 24 compliance

## OPTIONS

- Range of lumen packages and color temperatures
- Tunable white (2700K - 6500K)
- Colored LEDs, including True/Native Amber
- Sensors and controls
- Lens options
- Antimicrobial finish
- Wet location
- Emergency battery pack
- Tamper-proof screws
- Customization available upon request



**Los Angeles Lighting Mfg. Co.**  
 Contact Us  
 T: 626-454-8300 10141 Olney Street  
 F: 626-454-8399 El Monte, CA 91731  
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 03/28/25




ORDERING INFORMATION: Additional Options Available. Visit [www.lalighting.com/resources](http://www.lalighting.com/resources) for more information

EXAMPLE: GCR210-4-4L-FSW-PA2-BPL1.5-DRDM-UNV-1/840

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	FINISH	DOOR FRAME	OPTICAL	MECHANICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
GCR210		4L								1	
<b>GCR210</b> • Class 100 Cleanroom Grid LED Luminaire	2 - 2000 lm 4 - 4000 lm 6 - 6000 lm 8 - 8000 lm 12 - 12000 lm  <b>High Efficacy</b> 2HE - 2000 lm 4HE - 4000 lm 6HE - 6000 lm	4L • 4'	<b>AMF</b> • Antimicrobial Finish  *Leave blank if not specified	<b>FSW</b> • Flat Steel White Enamel Door Frame	<b>PA2</b> • Clear Prismatic Acrylic 0.125"  <b>FPA2</b> • Frosted Prismatic Acrylic 0.125"  <b>DRP8</b> • High-Impact Clear Prismatic Acrylic 0.187"  <b>FFWA</b> • Flat Frosted White Acrylic	<b>WL</b> • Wet Location  <b>TP</b> • Tamper Proof Screws (Hex Socket with Post)  *Leave blank if not specified	<b>BPL1.5</b> • 1500 lm emergency battery pack  *Leave blank if not specified	<b>DRDM</b> • 0-10V Dimming Driver  <b>DRDM2C</b> • 2-Channel 0-10V Dimming Driver (for Color Tunable White)  <b>DRSD</b> • Step Dimming Driver  <b>DR2W</b> • 120V 2-Wire Phase Dimming Driver (Must Specify 120V in Voltage Column)	<b>UNV</b> • 120V-277V	1 • One LED Row	<b>827</b> • 80+CRI / 2700K  <b>830</b> • 80+CRI / 3000K  <b>835</b> • 80+CRI / 3500K  <b>840</b> • 80+CRI / 4000K  <b>850</b> • 80+CRI / 5000K  <b>865</b> • 80+CRI / 6500K  <b>8TW</b> • 80+CRI Tunable White 2700K-6500K Requires DRDM2C driver  <b>AM8<sup>1</sup></b> • PC Yellow 575 nm - 590 nm  <b>AM9<sup>1</sup></b> • PC Amber 586 nm - 593 nm  <b>AMT<sup>1</sup></b> • True Amber 585 nm - 595 nm
Standard options for GCR210 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit <a href="http://www.lalighting.com/resources">www.lalighting.com/resources</a> or contact customer service.											<b>90CRI Also available</b>  Contact customer service for additional CRI/CCT packages.
<sup>1</sup> For amber and other color LEDs, available lumen packages vary. Contact customer service for more information.											

DOOR FRAME

CROSS SECTION



FEATURES

- Full Length Piano Hinge
- Inverted Lens
- Two 10-24 Captive Machine Screws
- Sealed with Closed Cell Neoprene Gasket

FS

W

FINISHES

- W** White Enamel
- B** Black Enamel

STYLES

- FS** Flat Steel

OPTICAL OPTIONS

STANDARD LENSES FOR GCR210 - Prismatic lenses are inverted to position the flat side facing down.

- PA2** Clear Prismatic Acrylic, Nom. 0.125" OA Thickness, Female Prisms 3/16" Square Base, Pattern 12
- FPA2** Frosted Prismatic Acrylic, Nom. 0.125" OA Thickness, Female Prisms 3/16" Square Base, Pattern 12
- DRP8** High-Impact Clear Prismatic Acrylic, Nom. 0.187" OA Thickness, Female Prisms 3/16" Square Base, Pattern 12
- FFWA** Flat Frosted White Acrylic, No Thickness Specified



Los Angeles Lighting Mfg. Co.  
 Contact Us  
 T: 626-454-8300  
 F: 626-454-8399  
 www.lalighting.com  
 10141 Olney Street  
 El Monte, CA 91731  
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 03/28/25



SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

Normal Temp

4'	LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	GCR210-2-4L-FSW-PA2-DRDM-UNV-1/840	1478	12.5	118.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
	4000 Lumens (Nominal)	GCR210-4-4L-FSW-PA2-DRDM-UNV-1/840	2901	25.5	113.6 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
	6000 Lumens (Nominal)	GCR210-6-4L-FSW-PA2-DRDM-UNV-1/840	4282	39.1	109.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
	8000 Lumens (Nominal)	GCR210-8-4L-FSW-PA2-DRDM-UNV-1/840	5622	53.1	106.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
	12000 Lumens (Nominal)	GCR210-12-4L-FSW-PA2-DRDM-UNV-1/840	8563	78.0	109.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

Normal Temp High Efficacy

4'	LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	GCR210-2HE-4L-FSW-PA2-DRDM-UNV-1/840	1502	12.4	121.6 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
	4000 Lumens (Nominal)	GCR210-4HE-4L-FSW-PA2-DRDM-UNV-1/840	2955	24.9	118.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
	6000 Lumens (Nominal)	GCR210-6HE-4L-FSW-PA2-DRDM-UNV-1/840	4388	37.8	116.2 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*

NOTE:

System data as of 1/29/25 (K-Boards).

Luminaire efficiency: 69.3%

Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



**Los Angeles Lighting Mfg. Co.**  
 Contact Us  
 T: 626-454-8300 10141 Olney Street  
 F: 626-454-8399 El Monte, CA 91731  
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 03/28/25

