



# INDUSTRIAL

## IND220

SERIES 4FT, 8FT  
11" WIDE INDUSTRIAL LUMINAIRE




|      |  |
|------|--|
| JOB  |  |
| TYPE |  |
| DATE |  |


### SUSPENSION/SURFACE MOUNTED LED LUMINAIRE




#### CROSS SECTION



#### 4' BACKPLATE



#### 8' BACKPLATE



### SPECIFICATIONS

#### CONSTRUCTION

- 20 gauge cold-rolled steel housing
- 24 gauge cold-rolled steel reflector secured by quarter turn fasteners
- End plates fastened to housing by sheet metal screws to assure rigidity

#### FINISH

- Baked white polyester finish
- Minimum reflectance 86%

#### ELECTRICAL

- High efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF)  $\geq 0.9$
- Total Harmonic Distortion (THD)  $\leq 20\%$

#### LISTING

- UL USA and Canada listed / suitable for damp locations

#### WARRANTY

5-Year limited warranty standard. 10-Year limited warranty also available

### APPLICATIONS

- Warehouse, Industrial, Commercial

### FEATURES

- 0-10V Dimming driver standard
- Supports California Title 24 compliance

### OPTIONS CONTACT CUSTOMER SERVICE FOR ADDITIONAL OPTIONS

- Controls
- 14 gauge wire guard
- Emergency battery pack
- Tunable white (2700K-6500K)
- Wireless Controls and sensors
- Customization available upon request



Los Angeles Lighting Mfg. Co.  
Contact Us  
T: 626-454-8300  
F: 626-454-8399  
www.lalighting.com  
10141 Olney Street  
El Monte, CA 91731  
Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 10/03/24



ORDERING INFORMATION

ADDITIONAL OPTIONS AVAILABLE. VISIT [WWW.LALIGHTING.COM/RESOURCES](http://WWW.LALIGHTING.COM/RESOURCES) FOR MORE INFORMATION

**EXAMPLE: IND220-4-4L-BPL1.5-DRDM-UNV-1/840**

| SERIES                                 | NOMINAL LED LUMENS                                       | NOMINAL LENGTH | CONTROLS  | ELECTRICAL   | DRIVER                                | VOLTAGE   | # OF LED ROWS           | CRI / CCT  |
|--|--|----------------|---|--|---------------------------------------|---|-------------------------|--|
| <b>IND220</b>                          |  |                |   |  |                                       |   | <b>1</b>                |  |
| <b>IND220</b><br>• 11" Wide Industrial | 2 - 2000lm<br>4 - 4000lm<br>6 - 6000lm<br>8 - 8000lm     | 4<br>• 4L      | <b>MS(xx)</b><br>• Motion Sensor<br>• Lens Option<br><br><b>WLC(LED RU)</b><br>• Wireless Control | <b>BPL1.5</b><br>• Emergency Battery Pack 1500 lm<br><br>*Leave blank if not specified | <b>DRDM</b><br>• 0-10V Dimming Driver | <b>UNV</b><br>• 120V-277V<br><br><b>120V</b><br>• 120 Volt<br><br><b>277V</b><br>• 277 Volt<br><br><b>347V</b><br>• 347 Volt<br><br><b>480V</b><br>• 480 Volt | <b>1</b><br>• 1 LED Row | <b>827</b><br>• 80+CRI / 2700K<br><br><b>830</b><br>• 80+CRI / 3000K<br><br><b>835</b><br>• 80+CRI / 3500K<br><br><b>840</b><br>• 80+CRI / 4000K<br><br><b>850</b><br>• 80+CRI / 5000K<br><br><b>865</b><br>• 80+CRI / 6500K<br><br><b>8TW</b><br>• 80+CRI Tunable White 2700K-6500K<br><br><b>90CRI Also available</b><br><br>Contact customer service for additional CRI/CCT packages. |
|  | 4 - 4000lm<br>8 - 8000lm<br>12 - 12000lm<br>16 - 16000lm | 8<br>• 8L      | *Leave blank if not specified   |  |                                       |   |                         |  |

Standard options for IND220 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit [www.lalighting.com/resources](http://www.lalighting.com/resources) or contact customer service.

SYSTEM DATA

ADDITIONAL LUMEN PACKAGES AVAILABLE. CONTACT CUSTOMER SERVICE FOR MORE INFORMATION

| 4' - LED LUMEN PACKAGE | NORMAL AMBIENT TEMPERATURE PRODUCT CODE | DELIVERED LUMENS | SYSTEM WATTS | LUMINAIRE EFFICACY | AMBIENT TEMP.              | FLUORESCENT EQUIVALENT | IES FILES |
|------------------------|---|------------------|--------------|--------------------|----------------------------|------------------------|-----------|
| 2000 Lumens (Nominal)  | IND220-2-4L-DRDM-UNV-1/840              | 2117 lm          | 16.6         | 127.6 lm/W         | -20°C / 35°C (-4°F / 95°F) | 1-F32T8                | *         |
| 4000 Lumens (Nominal)  | IND220-4-4L-DRDM-UNV-1/840              | 4041 lm          | 34.7         | 116.5 lm/W         | -20°C / 35°C (-4°F / 95°F) | 2-F32T8, 1-F54T5HO     | *         |
| 6000 Lumens (Nominal)  | IND220-6-4L-DRDM-UNV-1/840              | 5984 lm          | 52.2         | 114.6 lm/W         | -20°C / 35°C (-4°F / 95°F) | 3-F32T8                | *         |
| 8000 Lumens (Nominal)  | IND220-8-4L-DRDM-UNV-1/840              | 8028 lm          | 66.4         | 120.9 lm/W         | -20°C / 35°C (-4°F / 95°F) | 4-F32T8, 2-F54T5HO     | *         |

| 8' - LED LUMEN PACKAGE | NORMAL AMBIENT TEMPERATURE PRODUCT CODE | DELIVERED LUMENS | SYSTEM WATTS | LUMINAIRE EFFICACY | AMBIENT TEMP.              | FLUORESCENT EQUIVALENT | IES FILES |
|------------------------|---|------------------|--------------|--------------------|----------------------------|------------------------|-----------|
| 4000 Lumens (Nominal)  | IND220-4-4L-DRDM-UNV-1/840              | 4265 lm          | 33.2 W       | 128.9 lm/W         | -20°C / 35°C (-4°F / 95°F) | 2-F32T8                | *         |
| 8000 Lumens (Nominal)  | IND220-8-4L-DRDM-UNV-1/840              | 8079 lm          | 68.1 W       | 118.6 lm/W         | -20°C / 35°C (-4°F / 95°F) | 4-F32T8, 2-F54T5HO     | *         |
| 12000 Lumens (Nominal) | IND220-12-4L-DRDM-UNV-1/840             | 11826 lm         | 89.1 W       | 132.9 lm/W         | -20°C / 35°C (-4°F / 95°F) | 6-F32T8                | *         |
| 16000 Lumens (Nominal) | IND220-16-4L-DRDM-UNV-1/840             | 16178 lm         | 134.1 W      | 120.6 lm/W         | -20°C / 35°C (-4°F / 95°F) | 8-F32T8, 4-F54T5HO     | *         |

**NOTE:**  
System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application.  
This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.  
Additional lumen packages and color temperatures available.



**Los Angeles Lighting Mfg. Co.**  
Contact Us  
T: 626-454-8300  
F: 626-454-8399  
www.lalighting.com  
10141 Olney Street  
El Monte, CA 91731  
Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.  
Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.


Revised: 10/03/24




MADE IN THE USA  
BAA Compliant

**MOUNTING ACCESSORIES**


**Y-TOGGLE-END / CABLE SUSPENSION SYSTEM**



**CABLE SUSPENSION SYSTEM**




**V-HOOK / CABLE SUSPENSION SYSTEM**



**CHAIN MOUNT COUPLING**

- Chain mount coupling with lift-up tabs for installation of V-Hooks when chain mounted
- Baked white enamel finish



CMC-245

| LUMINAIRE MODEL | CAT. NO. |
|-----------------|----------|
| IND220          | CMC-245  |

**ACCESSORIES**

**WGN14-IND220-4**

- 14 gauge Wire Guard
- Chrome epoxy powder coated finish
- Two wire guards required for 8' luminaire



**Los Angeles Lighting Mfg. Co.**  
 Contact Us  
 T: 626-454-8300  
 F: 626-454-8399  
 www.lalighting.com

10141 Olney Street  
 El Monte, CA 91731  
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 10/03/24



MADE IN THE USA  
 BAA Compliant