




# SECURITY GSE110



GRID-MOUNTED SECURITY LUMINAIRE

JOB	
TYPE	
DATE	


Commercial / Office / Classroom / Corridor



COMPATIBLE T-BAR GRIDS	
WIDTH	HEIGHT
15/16"	1 1/2"




## CROSS SECTION



⊕⊕ Access Plate

⊕ 7/8" Offset KO

## 4' BACKPLATE



## SPECIFICATIONS

### Construction

- 20 gauge cold-rolled steel welded housing
- 20 gauge cold-rolled steel door frame secured by stainless steel piano hinge and 2 captive stainless steel tamper proof screws
- Inner frame lens retainer rail
- One way polyurethane gasket standard

### Finish

- Painted after fabrication
- Baked white powder-coated finish
- Minimum reflectance 90%

### Optical

- High-impact clear prismatic acrylic lens (nominal 0.187) standard

### Electrical

- High-efficiency drivers coupled with long-life LEDs
- Service life tested at 148,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) ≤ 20%

### Listing

- UL USA and Canada listed / suitable for damp locations

### Warranty

- 5-Year limited warranty standard. 10-Year limited warranty also available

## APPLICATIONS

- Security, Office, Classroom, Public Areas, Commercial

## FEATURES

- 0-10V dimming driver standard
- Supports California Title 24 compliance

## OPTIONS

- Range of lumen packages and color temperatures
- Sensors and controls
- Lens options
- Painted after fabrication
- Tunable white (2700K – 6500K)
- Emergency battery pack
- Neoprene gasket
- Customization available upon request



**Los Angeles Lighting Mfg. Co.**  
 Contact Us  
 T: 626-454-8300 10141 Olney Street  
 F: 626-454-8399 El Monte, CA 91731  
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 04/01/25




ORDERING INFORMATION: Additional Options Available. Visit [www.lalighting.com/resources](http://www.lalighting.com/resources) for more information

EXAMPLE: GSE110-6-4L-FSW-DRP8-BPL1.5-DRDM-UNV-1/840

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	DOOR FRAME	OPTICAL	MECHANICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
GSE110		4L							1	
<b>GSE110</b> • High Impact Grid Security Luminaire	2 - 2000 lm 4 - 4000 lm 6 - 6000 lm 8 - 8000 lm 12 - 12000 lm  <b>High Efficacy</b> 2HE - 2000 lm 4HE - 4000 lm 6HE - 6000 lm	4L • 4'	<b>FSW</b> • Flat Steel White Enamel Door Frame	<b>DRP8</b> • High Impact Clear Prismatic Acrylic Nominal 0.187"  <b>DRP2</b> • High Impact Clear Prismatic Acrylic Nominal 0.125"  <b>PPC2</b> • Clear Prismatic Polycarbonate Nominal 0.125"	<b>GSKN1</b> • One-Way Neoprene Gasket  *Leave blank for standard One-Way Polyurethane Gasket	<b>BPL1.5</b> • 1500 lm emergency battery pack  <b>MS(xx)</b> • Motion Sensor  <b>WLC(LED RU)</b> • EnOcean Wireless Control  *Leave blank if not specified	<b>DRDM</b> • 0-10V Dimming Driver  <b>DRDM2C</b> • 2-Channel 0-10V Dimming Driver (for Color Tunable White)  <b>DRSD</b> • Step Dimming Driver  <b>DR2W</b> • 120V 2-Wire Phase Dimming Driver (Must Specify 120V in Voltage Column)	<b>UNV</b> • 120V-277V	1 • One LED Row	<b>827</b> • 80+CRI / 2700K  <b>830</b> • 80+CRI / 3000K  <b>835</b> • 80+CRI / 3500K  <b>840</b> • 80+CRI / 4000K  <b>850</b> • 80+CRI / 5000K  <b>865</b> • 80+CRI / 6500K  <b>8TW</b> • 80+CRI Tunable White 2700K-6500K Requires DRDM2C driver  <b>90CRI Also available</b>  Contact customer service for additional CRI/CCT packages.
Standard options for GSE110 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit <a href="http://www.lalighting.com/resources">www.lalighting.com/resources</a> or contact customer service.										

DOOR FRAME CROSS SECTION



FEATURES

- Full Length Piano Hinge
- Two Captive Tamper Proof Screws (Hex Socket with Post)
- Inner Frame Lens Retainer Rail

FS W

FINISHES

W White Enamel

STYLES

FS Flat Steel

OPTICAL OPTIONS

STANDARD LENSES FOR GSE110

- DRP8** High Impact Clear Prismatic Acrylic, Nom. 0.187" OA Thickness, Female Prisms 3/16 Square Base
- DRP2** High Impact Clear Prismatic Acrylic, Nom. 0.125" OA Thickness, Female Prisms 3/16 Square Base
- PPC2** Clear Prismatic Polycarbonate, Nom. 0.125" OA Thickness, Female Prisms 3/16 Square Base



Los Angeles Lighting Mfg. Co.  
 Contact Us  
 T: 626-454-8300  
 F: 626-454-8399  
 www.lalighting.com  
 10141 Olney Street  
 El Monte, CA 91731  
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 04/01/25




## NEOPRENE GASKET

If Neoprene gasketing is not specified, standard one-way polyurethane gasket will be used.


### One-Way

Gasket between housing and door frame.



### Two-Way

Additional gasket between housing and grid.



## SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

Normal Temp	4'	LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
		2000 Lumens (Nominal)	GSE110-2-4L-DRP8-DRDM-UNV-1/840	1478	12.5	118.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
		4000 Lumens (Nominal)	GSE110-4-4L-DRP8-DRDM-UNV-1/840	2901	25.5	113.6 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
		6000 Lumens (Nominal)	GSE110-6-4L-DRP8-DRDM-UNV-1/840	4282	39.1	109.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
		8000 Lumens (Nominal)	GSE110-8-4L-DRP8-DRDM-UNV-1/840	5622	53.1	106.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
		12000 Lumens (Nominal)	GSE110-12-4L-DRP8-DRDM-UNV-1/840	8563	78.0	109.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

Normal Temp High Efficacy	4'	LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
		2000 Lumens (Nominal)	GSE110-2HE-4L-DRP8-DRDM-UNV-1/840	1502	12.4	121.6 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
		4000 Lumens (Nominal)	GSE110-4HE-4L-DRP8-DRDM-UNV-1/840	2955	24.9	118.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
		6000 Lumens (Nominal)	GSE110-6HE-4L-DRP8-DRDM-UNV-1/840	4388	37.8	116.2 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*

**NOTE:**  
System data as of 4/1/25 (K-Boards).  
Luminaire efficiency: 1x4 - 69.3%  
Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



**Los Angeles Lighting Mfg. Co.**  
Contact Us  
T: 626-454-8300 10141 Olney Street  
F: 626-454-8399 El Monte, CA 91731  
www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 04/01/25

