



# WET LOCATION LED

## FWL320 (2X4) SERIES (2X2 AVAILABLE)



TRIM FLANGE WET LOCATION LUMINAIRE

DATE	
JOB	

WWW.LALIGHTING.COM  
626-454-8300

### RECESSED MOUNTED WET LOCATION LED LUMINAIRE

### DIMENSIONS



### APPLICATIONS

- Wet Location, Covered Ceiling, Commercial

### FEATURES

- Wet location (UL listed with sprinkler test)
- 0-10V dimming driver standard (See *DRIVER OPTIONS* for other dimming types)
- Supports California Title 24 compliance

### OPTIONS

- Full customization available upon request
- Additional lumen packages and color temperatures available
- Controls and sensors available (See *SENSOR OPTIONS* for controls and sensors)
- Wireless control options available (See *SENSOR OPTIONS* for wireless controls)
- Variety of lenses available (See *OPTICAL OPTIONS* for lenses)
- Emergency battery pack available (See *BATTERY PACK OPTIONS* for battery pack options)
- Antimicrobial finished housing and door frame available
- Tamper proof screws available
- Hanger yokes available (See *ACCESSORIES* for details)
- Tunable white available (2700K-6500K)

### SPECIFICATIONS

#### CONSTRUCTION

- 22 ga. electro-galvanized steel welded housing
- All parts fitted and sealed, no unused holes or knockouts
- 20 ga. electro-galvanized steel door frame secured by full length piano hinge and 2 captive screws
- Door frame and lens sealed with closed cell neoprene gasket
- 18 ga. trim flange

#### FINISH

- Baked white powder coated finish / welded and painted after fabrication / minimum reflectance 90%

#### OPTICAL

- Inverted clear prismatic acrylic lens (nominal 0.125) standard

#### ELECTRICAL

- High efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000-51,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF)  $\geq 0.9$
- Total Harmonic Distortion (THD)  $\leq 20\%$

#### LISTING

- UL USA and Canada listed / suitable for wet locations / UL listed with sprinkler test

#### WARRANTY

- 5-year limited warranty



Los Angeles Lighting Mfg. Co.

Contact Us  
T: 626-454-8300 10141 Olney Street  
F: 626-454-8399 El Monte, CA 91731  
www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2022 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/11/19



MADE IN THE USA  
BAA Compliant

ORDERING INFORMATION

EXAMPLE: FWL320-12-4L-FSW-PA2-BPL 1.5-DRDM-UNV-2/840

SERIES	LED LUMEN PACKAGE	EFFICACY	NOMINAL LENGTH	FINISH	DOOR FRAME	OPTICAL	MECHANICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROW	CRI / CCT
<b>FWL320</b>			<b>4L</b>						<b>DRDM</b>	<b>UNV</b>	<b>2</b>	
<b>FWL320</b> Trim Flange Wet Location LED Luminaire	2 Nom. 2000 Lumens 4 Nom. 4000 Lumens 6 Nom. 6000 Lumens 8 Nom. 8000 Lumens 12 Nom. 12000 Lumens  <i>*Additional Lumen Packages Available</i>	(Blank) Standard  <b>HE</b> High Efficacy	<b>4L</b> 2' x 4'	<b>AMF</b> Antimicrobial Finished Housing and Door Frame  <i>*Leave Blank if Not Specified</i>	<b>FSW</b> Flat Steel White Enamel Door Frame  See <b>DOOR FRAME</b> for Options	<b>PA2</b> Clear Prismatic Acrylic 0.125 Nominal  <b>DRP8</b> High Impact Clear Prismatic Acrylic 0.187 Nominal  <b>FPA2</b> Frosted Prismatic Acrylic 0.125 Nominal  See <b>OPTICAL OPTIONS</b> for Options	<b>TP</b> Tamper Proof Screws (Hex Socket with Post)  <i>*Leave Blank if Not Specified</i>  <i>Additional Mechanical Options</i>	<b>BPL1.5</b> Emergency Battery Pack, Nom. 1500 lm  See <b>BATTERY PACK OPTIONS</b> for Options  <b>WLC(LEDPU)</b> EnOcean Wireless Control  See <b>SENSOR OPTIONS</b> for Options  <i>*Leave Blank if Not Specified</i>  <i>Additional Electrical Options</i>	<b>DRDM</b> 0-10V Dimming Driver  See <b>DRIVER OPTIONS</b> for Options	<b>UNV</b> 120V-277V  See <b>DRIVER OPTIONS</b> for Options	<b>2</b> Two LED Rows	<b>830</b> 80+CRI / 3000K Color Temp.  <b>835</b> 80+CRI / 3500K Color Temp.  <b>840</b> 80+CRI / 4000K Color Temp.  <b>850</b> 80+CRI / 5000K Color Temp.  <i>*Additional Color Temp. Available</i>

SYSTEM DATA

LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	FWL320-2-4L-FSW-PA2-DRDM-UNV-2/840	1727	12.4	139.8 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
4000 Lumens (Nominal)	FWL320-4-4L-FSW-PA2-DRDM-UNV-2/840	3399	24.9	136.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	FWL320-6-4L-FSW-PA2-1DRDM-UNV-2/840	5046	37.8	133.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	FWL320-8-4L-FSW-PA2-DRDM-UNV-2/840	6671	50.9	131.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	FWL320-12-4L-FSW-PA2-DRDM-UNV-2/840	9849	78.0	126.3 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	FWL320-2HE-4L-FSW-PA2-DRDM-UNV-2/840	1765	12.2	144.2 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
4000 Lumens (Nominal)	FWL320-4HE-4L-FSW-PA2-DRDM-UNV-2/840	3454	24.6	140.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	FWL320-6HE-4L-FSW-PA2-DRDM-UNV-2/840	4797	34.6	138.7 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	FWL320-8HE-4L-FSW-PA2-DRDM-UNV-2/840	6464	47.2	137.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	FWL320-12HE-4L-FSW-PA2-DRDM-UNV-2/840	9765	72.8	134.1 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

**NOTE:**  
System data as of 4/24/25 (K-Boards).  
Luminaire efficiency: 79.7%  
Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



**Los Angeles Lighting Mfg. Co.**  
Contact Us  
T: 626-454-8300 10141 Olney Street  
F: 626-454-8399 El Monte, CA 91731  
www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2022 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/11/19



**SENSOR OPTIONS**



**CONTROLS AND SENSORS**

**WLC(LED RU) - EnOcean® LED Relay Zone Controller**

- Supports a single LED fixture or multiple daisy chained LED fixtures
- Module installed inside lighting fixture

**ESRPU-W-EO - EnOcean® Rocker Switch – Single – Surface Mount**

- Wireless single rocker switch with mounting plate
- No batteries needed

**EDRPU-W-EO - EnOcean® Rocker Switch – Double – Surface Mount**

- Wireless double rocker switch with mounting plate
- No batteries needed

**S3054-N300 - EnOcean® Navigan NWC 300U – Commissioning Tool**

- Navigan Wireless Commissioner is used to configure EnOcean controllers & sensors
- It can be used to define link tables, change parameters/settings, and to edit & store projects
- Configuration settings can be saved and cloned to enable quick configuration
- Connectivity is through the NWC 300U USB Stick

**EOSWU-W-EO - EnOcean® Occupancy Sensor – Wall Mount**

- Wireless wall mounted occupancy sensor
- Solar powered - no batteries needed (coin battery operated in low light conditions)
- PIR motion sensor with both wide angle (50') and long range (100') options
- Mounting height: 6-8 feet

**EOSCU-W-EO - EnOcean® Occupancy Sensor – Ceiling Mount**

- Wireless ceiling mounted occupancy sensor
- Solar powered - no batteries needed (coin battery operated in low light conditions)
- PIR motion sensor with 360 degree viewing angle lens (34' diameter)
- Mounting height: 7-10 feet

**ELLSU-W-EO - EnOcean® Light Level Sensor – Ceiling Mount**

- Light Level sensor that measures and reports the level of available natural light
- Solar powered - no batteries needed (coin battery operated in low light conditions)
- Enables implementation of daylight harvesting control systems
- Mounting position: At the ceiling, close to ambient light source

**DRIVER OPTIONS**

PLEASE CONSULT FACTORY TO SEE IF YOUR SELECTED DRIVER OPTION WORKS WITH THIS FIXTURE.

**DRDM – UNV**

\* Normal Stock Item

**VOLTAGE**

- 120V** 120 Volt
- 277V** 277 Volt
- UNV\*** Universal 120-277 Volt
- 347V** 347 Volt
- 480V** 480 Volt

**DRIVER TYPE**

- DRDM\*** 0-10V Dimming Driver
- DRDM1** 0-10V Dimming Driver, 1% Dimming
- DRDM2C** 2-Channel 0-10V Dimming Driver (for Color Tunable White)
- DR2W** 2-Wire Phase Dimming Driver
- DRDA** Digital Addressable DALI Dimming Driver
- DRDA2C** Digital Addressable DALI Type8 2-Channel Driver (for Color Tunable White)
- DRDA2.0** Digital Addressable DALI 2.0 Dimming Driver
- DRDA2.02C** Digital Addressable DALI 2.0 Type8 2-Channel Driver (for Color Tunable White)
- DRSD** Step Dimming Driver
- DR(LTEA2W)** Lutron® 2-Wire 1% Dimming Driver (120V Forward Phase only)
- DR(LDE1)** Lutron® EcoSystem 1% Soft-On, Fade-to-Black™ Dimming Driver
- DR(LDE5)** Lutron® EcoSystem 5% Dimming Driver
- DR(PEQ0)** Lutron® EcoSystem 0.1% Soft-On, Fade-to-Black Dimming Driver
- DR(PSQ0)** Lutron® T-Series Digital 1% Dimming 2-Channel Driver (for Color Tunable White)

**# OF DRIVERS SPECIFIED**

- (Blank)** Not Specified
- #** Number of Drivers Specified per Lighting Fixture

**BATTERY PACK OPTIONS**

PLEASE CONSULT FACTORY TO SEE IF YOUR SELECTED BATTERY PACK OPTION WORKS WITH THIS FIXTURE.

**BPL**

**LUMEN PACKAGE**

- 0.7** Nominal 750 Lumens
- 1.5** Nominal 1500 Lumens
- 3.0** Nominal 3000 Lumens

\*Additional lumen packages available

**TYPE**

- (Blank)** Normal Ambient Temp. / Standard Operation
- C** Cold Environment (-20°C)
- F** With Flex for Remote Mounting
- SL** Slim Casing
- ST** Self Test / Diagnostic

\*Additional options available



**Los Angeles Lighting Mfg. Co.**

Contact Us  
 T: 626-454-8300 10141 Olney Street  
 F: 626-454-8399 El Monte, CA 91731  
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2022 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/11/19



**MADE IN THE USA**  
BAA Compliant


**OPTICAL OPTIONS**

**STANDARD LENSES FOR FWL320**

<b>PA2</b>	Clear Prismatic Acrylic, Nom. 0.125 OA Thickness, Female Prisms 3/16 Square Base
<b>DRP8</b>	High Impact Clear Prismatic Acrylic, Nom. 0.187 OA Thickness, Female Prisms 3/16 Square Base
<b>FPA2</b>	Frosted Prismatic Acrylic, Nom. 0.125 OA Thickness


**DOOR FRAME**

CROSS SECTION



**FEATURES**

- Full Length Piano Hinge
- Inverted Lens
- Two 10-24 Captive Machine Screws
- Sealed with Closed Cell Neoprene Gasket





**ACCESSORIES**

**HS-24\_1/2**

- Hanger Yokes
- Compatible with all types of recessed flanged fixtures
- 1/4 - 20 x 3" machine screws locate into knockout on back of fixture housing
- Two (2) per fixture

Note: Must drill own holes. Caulking compound should be used to seal the holes.



**Los Angeles Lighting Mfg. Co.**  
 Contact Us  
 T: 626-454-8300 10141 Olney Street  
 F: 626-454-8399 El Monte, CA 91731  
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2022 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/11/19

