



RECESSED MOUNTED LED LUMINAIRE FOR 1" OR $1_1/2$ " WIDE INVERTED T-BAR CEILINGS

1_1/2"

DIMENSIONS





APPLICATIONS

· Commercial, Architectural, Retail

FEATURES

- 0-10V dimming driver standard
- · Supports California Title 24 compliance

OPTIONS

- Full customization available upon request
- · Additional lumen packages and color temperatures available
- Wireless control options available
- Emergency battery pack available
- 20 ga. cold rolled steel housing available

SPECIFICATIONS

CONSTRUCTION

- 22 ga. cold rolled steel housing
- High reflectance low gloss white reflector

FINISH

 \bullet Baked white powder coated finish / minimum reflectance 90% / painted after fabrication

ELECTRICAL

- · High efficiency drivers coupled with long-life LEDs
- Service life greater than 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) ≤ 20%

LISTING

• UL USA and Canada listed / suitable for damp locations

WARRANTY

• 5-Year limited warranty standard. 10-Year limited warranty also available



Los Angeles Lighting Mfg. Co.





Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.





ORDERING INFORMATION **EXAMPLE:** GWW210-4-2L-BPL1.5-DRDM-UNV-1/840

SERIES	LED LUMEN PACKAGE	EFFICACY	NOMINAL LENGTH	MECHANICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROW	CRI / CCT
GWW210			2L			DRDM	UNV	1	
GWW210 Wall Wash Grid LED Luminaire	2 Nom. 2000 Lumens 4 Nom. 4000 Lumens *Additional Lumen Packages Available	(Blank) Standard HE High Efficacy	2L 2'	20G 20 ga. Cold Rolled Steel Housing *Leave Blank if Not Specified	BPL1.5 1500lm Emergency Battery Pack WLC(xxxxx) Wireless Control *Leave Blank if Not Specified Additional Electrical Options	DRDM 0-10V Dimming Driver	UNV 120V-277V	1 One LED Row	830 80+CRI / 3000K Color Temp. 835 80+CRI / 3500K Color Temp. 80+CRI / 4000K Color Temp. 850 80+CRI / 5000K Color Temp.
including lum	Standard options for GWW210 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.								*Additional Color Temp. Available

SYSTEM DATA

THESE ARE THE MOST POPULAR LUMEN PACKAGES. PLEASE CONSULT FACTORY FOR ADDITIONAL SYSTEM DATA.

LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GWW210-2-2L-DRDM-UNV-1/840	*	*	*	-20°C / 35°C	2-F17T8, 1-F24T5HO	*
4000 Lumens (Nominal)	GWW210-4-2L-DRDM-UNV-1/840	*	*	*	-20°C / 35°C	4-F17T8, 2-F24T5HO	

LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GWW210-2HE-2L-DRDM-UNV-1/840	*	*	*	-20°C / 35°C	2-F17T8, 1-F24T5HO	*
4000 Lumens (Nominal)	GWW210-4HE-2L-DRDM-UNV-1/840	*	*	*	-20°C / 35°C	4-F17T8, 2-F24T5HO	*

NOTE:

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application.

This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



Contact Us T: 626-454-8300 F: 626-454-8399 www.lalighting.com







Revised: 07/07/23