



Surface-mounted/suspended LED strip




- ϕ 7/8" KO
- ϕ 1/16" Stem Mounting KO
- 3/16" Mounting KO
- V-Hook Hole


2' BACKPLATE




3' BACKPLATE




4' BACKPLATE



6' BACKPLATE



8' BACKPLATE



SPECIFICATIONS

Construction

- 22 gauge cold-rolled steel housing
- End plates fastened to housing by sheet metal screws to assure rigidity

Finish

- Baked white polyester finish
- Minimum reflectance 86%
- End plates: painted after fabrication, baked white powder-coated finish

Optical

- Frosted white acrylic lens

Electrical

- High-efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000 hours (L70)
- Universal voltage 120-277V, 50-60Hz (347V, 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) $\leq 20\%$

Listing

- UL USA and Canada listed / suitable for damp locations

Warranty

- 5-Year limited warranty standard. 10-Year limited warranty also available

APPLICATIONS

- Retail, Warehouse, Industrial, Office, Corridor, Stairwell, Parking Structure, Assembly Line, Aisle Lighting

FEATURES

- 0-10V Dimming driver standard
- Supports California Title 24 compliance
- End caps may be used as couplings for seamless row mounting on surfaces

OPTIONS

- Sensors and controls
- Cord & plug
- Custom housing colors
- Emergency battery pack
- Tunable white (2700K - 6500K)
- Plug-in branch wiring connector system
- Customization available upon request

ORDERING INFORMATION: Additional Options Available. Visit www.lalighting.com/resources for more information**EXAMPLE:** STW100-8-8L-FRWA-BPLSL1.5-DRDM-UNV-1/840

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	COLOR	OPTICAL	CONTROLS	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
STW100							DRDM	UNV	1	
STW100 • 2 1/4" Wide LED Strip	1 1000lm 2 2000lm 3 3000lm 4 4000lm 5 5000lm High Efficacy 1HE 1000lm 2HE 2000lm 3HE 3000lm	2L • 2'	(Blank) • Standard White Housing BLK • Black Housing BZ • Bronze Housing	FRA • Frosted Acrylic FRWA • Frosted White Acrylic	MS(xx) • Motion Sensor • Lens Option WLC(LED RU) • Wireless Control WLC(AWNR-WH) • Lutron Athena wireless node (RF) WLC(AWNS-WH) • Lutron Athena wireless node w/sensor *Additional Lutron options on page (8) *Leave blank if not specified	BPLSL1.5 • 1500 lm Emergency Battery Pack, Slim Casing *Leave Blank if Not Specified (See Electrical Options page for more information on Plug-In Branch Wiring and Cord/Conduit Options)	DRDM • 0-10V Dimmable Driver	UNV • 120-277V, 50-60Hz	1 • 1 LED Row	827 • 80+CRI / 2700K 830 • 80+CRI / 3000K 835 • 80+CRI / 3500K 840 • 80+CRI / 4000K 850 • 80+CRI / 5000K 865 • 80+CRI / 6500K 8TW • 80+CRI Tunable White 2700K-6500K 90CRI Also available Contact customer service for additional CRI/ CCT packages.
	1.5 1500lm 3 3000lm 4.5 4500lm 6 6000lm	3L • 3'								
	2 2000lm 4 4000lm 6 6000lm 8 8000lm 10 10000lm High Efficacy 2HE 2000lm 4HE 4000lm 6HE 6000lm	4L • 4'								
	3 3000lm 6 6000lm 9 9000lm 12 12000lm High Efficacy 3HE 3000lm 6HE 6000lm 9HE 9000lm 12HE 12000lm	6L • 6'								
	4 4000lm 8 8000lm 12 12000lm 16 16000lm 20 20000lm High Efficacy 4HE 4000lm 8HE 8000lm 12HE 12000lm	8L • 8'								
Standard options for STW100 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.										



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300
 F: 626-454-8399
www.lalighting.com
 10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
 Please visit our website to view the most current information.


© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24




MOUNTING ACCESSORIES


Y-TOGGLE-END / CABLE SUSPENSION SYSTEM



CABLE SUSPENSION SYSTEM




V-HOOK / CABLE SUSPENSION SYSTEM



V-HOOK

- Hooks attach to V-Hook Holes on luminaire or chain mount coupling tabs
- Two (2) required per luminaire



FOR FIXTURE SERIES	CAT. NO
4" LEG HEIGHT (110/200/240/500) Series	V4

CHAIN MOUNT COUPLING

- Chain mount coupling with lift-up tabs for installation of V-Hooks when chain mounted
- Baked white enamel finish


CAT. NO.	FIXTURE SERIES
CMC-STW100	STW100 (only for 4ft & 8ft fixtures)




STEM (Specify Length)

- 3/8" IPS, nominal OD 5/8"
- Threaded 1" each end
- 2 lock nuts provided per stem
- Standard lengths: 6", 12", 18", 24", 30", 36", 48"
- Baked white enamel finish

Other lengths & finishes are available as specified



Stem Length Calculation



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300 10141 Olney Street
 F: 626-454-8399 El Monte, CA 91731
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
 Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED



Revised: 07/10/24



MOUNTING ACCESSORIES

CANOPY / CABLE SUSPENSION SYSTEM


- Self-locking, one-step adjustable suspension device with canopy




ELECTRICAL

PLUG-IN BRANCH WIRING CONNECTOR SYSTEM

- For wiring through fixture channel in single or multiple circuits
- Low-voltage for dimming available
- 12 gauge wire
- Quick connect plugs for easy installation
- Contact customer service for additional options



CORD & PLUG



**Consult local building codes for specific wet location installation requirements*



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300 10141 Olney Street
 F: 626-454-8399 El Monte, CA 91731
 www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
 Please visit our website to view the most current information.


© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24



ELECTRICAL

CORD & FLEXIBLE CONDUIT OPTIONS



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com

10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24



SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

2' Normal Ambient Temperature	2' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	1000 Lumens (Nominal)	STW100-1-2L-FRWA-DRDM-UNV-1/840	818	7.6	107.1 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F17T8	*
	2000 Lumens (Nominal)	STW100-2-2L-FRWA-DRDM-UNV-1/840	1606	14.1	113.7 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F17T8, 1-F24T5HO	LA-T3902b
	3000 Lumens (Nominal)	STW100-3-2L-FRWA-DRDM-UNV-1/840	2451	22.1	110.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F17T8	*
	4000 Lumens (Nominal)	STW100-4-2L-FRWA-DRDM-UNV-1/840	3256	27.3	119.4 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F17T8, 2-F24T5HO	*
	5000 Lumens (Nominal)	STW100-5-2L-FRWA-DRDM-UNV-1/840	3983	32.7	122.0 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F17T8, 2-F24T5HO	*

2' Normal Ambient Temp High Efficacy	2' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	1000 Lumens (Nominal)	STW100-1HE-2L-FRWA-DRDM-UNV-1/840	884	7.5	117.9 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F17T8	*
	2000 Lumens (Nominal)	STW100-2HE-2L-FRWA-DRDM-UNV-1/840	1572	12.4	127.1 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F17T8, 1-F24T5HO	*
	3000 Lumens (Nominal)	STW100-3HE-2L-FRWA-DRDM-UNV-1/840	2375	18.7	127.1 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F17T8	*

3' Normal Ambient Temperature	3' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	1500 Lumens (Nominal)	STW100-1.5-3L-FRWA-DRDM-UNV-1/840	1366	9.2	148.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
	3000 Lumens (Nominal)	STW100-3-3L-FRWA-DRDM-UNV-1/840	2428	17.8	136.1 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8, 1-F54T5HO	LA-T3634
	4500 Lumens (Nominal)	STW100-4.5-3L-FRWA-DRDM-UNV-1/840	3904	28.8	135.5 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F32T8	*
	6000 Lumens (Nominal)	STW100-6-3L-FRWA-DRDM-UNV-1/840	5027	39.1	128.6 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	*

4' Normal Ambient Temperature	4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	STW100-2-4L-FRWA-DRDM-UNV-1/840	1655	13.4	123.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
	4000 Lumens (Nominal)	STW100-4-4L-FRWA-DRDM-UNV-1/840	3249	26.7	121.7 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8, 1-F54T5HO	LA-T3632
	6000 Lumens (Nominal)	STW100-6-4L-FRWA-DRDM-UNV-1/840	5046	43.7	115.5 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F32T8	*
	8000 Lumens (Nominal)	STW100-8-4L-FRWA-DRDM-UNV-1/840	6565	51.1	128.4 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	*
	10000 Lumens (Nominal)	STW100-10-4L-FRWA-DRDM-UNV-1/840	8056	61.5	131.0 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	*

4' Normal Ambient Temp High Efficacy	4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	STW100-2HE-4L-FRWA-DRDM-UNV-1/840	1789	13.5	132.1 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
	4000 Lumens (Nominal)	STW100-4HE-4L-FRWA-DRDM-UNV-1/840	3180	23.5	135.6 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8, 1-F54T5HO	*
	6000 Lumens (Nominal)	STW100-6HE-4L-FRWA-DRDM-UNV-1/840	4805	36.4	132.0 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F32T8	*

NOTE:
System data as of 7/09/24.
Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24



SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

6' Normal Ambient Temperature	6' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	3000 Lumens (Nominal)	STW100-3-6L-FRWA-DRDM-UNV-1/840	2585	20.1	128.5 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F25T8, 3-F17T8	*
	6000 Lumens (Nominal)	STW100-6-6L-FRWA-DRDM-UNV-1/840	4896	39.0	125.5 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F25T8, 6-F17T8	*
	9000 Lumens (Nominal)	STW100-9-6L-FRWA-DRDM-UNV-1/840	7365	59.9	123.0 lm/W	-20°C / 35°C (-4°F / 95°F)	6-F25T8	*
6' Normal Ambient Temp High Efficacy	6' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	3000 Lumens (Nominal)	STW100-3HE-6L-FRWA-DRDM-UNV-1/840	2457	17.5	140.8 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F25T8, 3-F17T8	*
	6000 Lumens (Nominal)	STW100-6HE-6L-FRWA-DRDM-UNV-1/840	4855	34.4	141.1 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F25T8, 6-F17T8	*
	9000 Lumens (Nominal)	STW100-9HE-6L-FRWA-DRDM-UNV-1/840	7335	54.5	134.5 lm/W	-20°C / 35°C (-4°F / 95°F)	6-F25T8	*
8' Normal Ambient Temperature	12000 Lumens (Nominal)	STW100-12-6L-FRWA-DRDM-UNV-1/840	9919	81.8	121.2 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F39T5HO, 6-F24T5HO	*
	8' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	4000 Lumens (Nominal)	STW100-4-8L-FRWA-DRDM-UNV-1/840	3398	25.8	131.9 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8	*
	8000 Lumens (Nominal)	STW100-8-8L-FRWA-DRDM-UNV-1/840	6673	52.7	126.7 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	LA-T3633
8' Normal Ambient Temp High Efficacy	12000 Lumens (Nominal)	STW100-12-8L-FRWA-DRDM-UNV-1/840	10090	81.9	123.2 lm/W	-20°C / 35°C (-4°F / 95°F)	6-F32T8, 3-F54T5HO	*
	16000 Lumens (Nominal)	STW100-16-8L-FRWA-DRDM-UNV-1/840	13235	99.2	133.4 lm/W	-20°C / 35°C (-4°F / 95°F)	8-F32T8, 4-F54T5HO	*
	20000 Lumens (Nominal)	STW100-20-8L-FRWA-DRDM-UNV-1/840	16546	123.0	134.6 lm/W	-20°C / 35°C (-4°F / 95°F)	8-F32T8, 4-F54T5HO	*
	8' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
8' Normal Ambient Temp High Efficacy	4000 Lumens (Nominal)	STW100-4HE-8L-FRWA-DRDM-UNV-1/840	3306	22.7	145.4 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8	*
	8000 Lumens (Nominal)	STW100-8HE-8L-FRWA-DRDM-UNV-1/840	6532	45.3	144.2 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	*
	12000 Lumens (Nominal)	STW100-12HE-8L-FRWA-DRDM-UNV-1/840	9867	71.1	138.7 lm/W	-20°C / 35°C (-4°F / 95°F)	6-F32T8, 3-F54T5HO	*

NOTE:


System data as of 11/16/23.

Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.

PHOTOMETRIC DATA



STW100-4-4L-FRWA-DRDM-UNV-1/840

TEST NO. = LA-T3632
 NO. OF LED ROWS = 1
 SYSTEM WATT (W) = 26.7
 CRI ≥ 80
 L70(Hrs.) ≥ 50,000
 PHOTOMETRY TYPE = C

ZONAL LUMEN SUMMARY

DEGREES	LUMENS	% LAMP	% FIXTURE
0-30	867	21	27
0-40	1401	34	43
0-60	2402	59	74
0-90	3077	75	95
90-120	158	4	5
90-150	172	4	5
90-180	172	4	5
0-180	3249	80	100.0

SPACING CRITERION

ALONG	ACROSS
1.13	1.17

Luminaire Output = 3249 lumens
 Luminaire Efficacy = 121.7 lm/W
 Luminaire Efficiency = 79.51%



Los Angeles Lighting Mfg. Co.

Contact Us
 T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com

10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
 Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24





WIRELESS CONTROLS

Vive Systems

Vive PowPak Wireless Fixture Controls

WLC(FCJS0) - PowPak Wireless Fixture Control

- RF only. For use with 0-10V drivers.
- One fixture control per luminaire, typically end-mounted via 1/2" KO.

WLC(FCJS0S) - PowPak Wireless Fixture Control with Sensor

- RF with daylight/occupancy sensing. For use with 0-10V drivers.
- One fixture control per luminaire, typically end-mounted via 1/2" KO.
- Sensor must be installed separately.

WLC(FCJSE) - PowPak EcoSystem Wireless Fixture Control

- RF only. For use with Lutron EcoSystem drivers.
- One fixture control per luminaire, typically end-mounted via 1/2" KO.

WLC(FCJSSES) - PowPak EcoSystem Wireless Fixture Control with Sensor

- RF with daylight/occupancy sensing. For use with Lutron EcoSystem drivers.
- One fixture control per luminaire, typically end-mounted via 1/2" KO.
- Sensor must be installed separately.

Vive PowPak Sensors

*FC-SENSOR - PowPak Occupancy/Daylight Sensor

- For luminaires with existing PowPak Wireless Fixture Controls.
- Turns luminaire ON/OFF based on motion. Adjusts lumen output in response to ambient light.
- Recommended mounting height: 8-12ft

*FC-VSENSOR - PowPak Vacancy/Daylight Sensor

- For luminaires with existing PowPak Wireless Fixture Controls.
- Turns luminaire OFF when area is vacant. Adjusts lumen output in response to ambient light.
- Recommended mounting height: 8-12ft.

Vive Integral Fixture Controls

WLC(VRF) - Vive Integral Wireless Fixture Control

- RF only. Requires controls-ready driver.
- One fixture control per luminaire, mounting location varies by luminaire.

WLC(VDO) - Vive Integral Wireless Fixture Control

- RF, plus daylight/occupancy sensing. Requires controls-ready driver.
- One fixture control per luminaire, mounting location varies by luminaire.
- Turns luminaire ON/OFF based on motion. Adjusts lumen output in response to ambient light.
- Coverage area at 9ft mounting height: Up to 300 sq.ft for major motions; 150 sq.ft. for minor motions.

How to Order

Pre-installed components are ordered by adding the part number to the luminaire:

GHL320-4-4L-FSW-PA- [WLC\(FCJS0\)](#) -DRDM-UNV-2/840

Components marked with * are ordered separately

Athena Wireless Nodes

Requires Athena-compatible drivers and Clear Connect Gateway - Type X

WLC(AWNR-WH) - Wireless Node (White)

- RF communication node. One per luminaire, integrally mounted.

WLC(AWNS-WH) - Wireless Node (White) with Sensor

- RF, plus daylight/occupancy sensing. One per luminaire, integrally mounted.

WLC(AWNR-BL) - Wireless Node (Black)

RF communication node. One per luminaire, integrally mounted.

WLC(AWNS-BL) - Wireless Node (Black) with Sensor

- RF, plus daylight/occupancy sensing. One per luminaire, integrally mounted.



WLC(AWNR-WH)
Athena Wireless Node



WLC(FCJS0)
PowPak Wireless Fixture Control



FC-SENSOR
PowPak Occupancy/Daylight Sensor



WLC(VDO)
Vive Integral Wireless Fixture Control

Lutron, Vive, Athena, PowPak, EcoSystem, Pico, and Clear Connect are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.



Los Angeles Lighting Mfg. Co.

Contact Us
T: 626-454-8300 10141 Olney Street
F: 626-454-8399 El Monte, CA 91731
www.lalighting.com Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 07/10/24

