


JOB	
TYPE	
DATE	

Recessed Parabolic Troffer for T-Bar Ceilings





CROSS SECTION



BACKPLATE

⊕ 7/8" K.O.

⊕ ACCESS PLATE



S6 LOUVER CONFIGURATION
(1 ROW, 6 CELLS)



SPECIFICATIONS

Construction

- 22 gauge cold-rolled steel housing
- Louvers secured to housing by T-hinges and latches
- One-way polyurethane gasket between housing and louver

Finish

- Baked white polyester finish
- Minimum reflectance 86%
- Parabolic louvers: semi-specular low iridescent aluminum finish

Optical

- Nominal 3" deep aluminum parabolic louvers
- Frosted white acrylic lens covering the LED Row

Electrical

- High-efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) ≤ 20%

Listing

- UL USA and Canada listed / suitable for damp locations

Warranty

- 5-Year limited warranty standard. 10-Year limited warranty also available

APPLICATIONS

- Commercial, Office

FEATURES

- 0-10V dimming driver standard
- Suitable for damp locations
- Supports California Title 24 compliance

OPTIONS

- Range of lumen packages and color temperatures
- Tunable white (2700K-6500K)
- White louvers (other colors also available)
- Wireless controls
- Emergency battery packs
- 20 gauge housing
- Customization available upon request

ORDERING INFORMATION: Additional Options Available. Visit www.lalighting.com/resources for more information

EXAMPLE: GPA610-4-4L-S6-DRDM-UNV-1/840									
SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	MATERIAL / FINISH	LOUVER CONFIGURATION	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
GPA610		4L		S6		DRDM	UNV	1	
GPA610 • Recessed Parabolic Troffer for T-Bar Ceilings High Efficacy 2HE - 2000lm 4HE - 4000lm 6HE - 6000lm Contact customer service for additional lumen packages	2 - 2000lm 4 - 4000lm 6 - 6000lm 8 - 8000lm	4L • 1' x 4'	20G • 20 Gauge Cold-Rolled Steel Housing <i>Leave blank for standard 22 gauge cold-rolled steel housing</i>	S6 • Semi-Specular Low Iridescent Aluminum; 1 Row of 6 Cells <i>White and other louver colors also available. Contact Customer Service.</i>	BPL1.5 • 1500 lm Emergency Battery Pack WLC(LED RU) • EnOcean Wireless Control *Leave blank if not specified	DRDM • 0-10V Dimming Driver	UNV • 120V-277V 120V • 120 Volt 277V • 277 Volt 347V • 347 Volt 480V • 480 Volt	1 • One LED Row	827 • 80+CRI / 2700K 830 • 80+CRI / 3000K 835 • 80+CRI / 3500K 840 • 80+CRI / 4000K 850 • 80+CRI / 5000K 865 • 80+CRI / 6500K 8TW • 80+CRI Tunable White 2700K-6500K 90CRI Also available Contact customer service for additional CRI/CCT packages, including 90 CRI
Standard options for GPA610 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.									

SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

Normal Ambient Temperature	4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	GPA610-2-4L-S6-DRDM-UNV-1/840	1531	13.4	114.2 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
	4000 Lumens (Nominal)	GPA610-4-4L-S6-DRDM-UNV-1/840	3007	26.7	112.6 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8, 1-F54T5HO	LA-T3925b
	6000 Lumens (Nominal)	GPA610-6-4L-S6-DRDM-UNV-1/840	4683	43.7	107.2 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F32T8	*
	8000 Lumens (Nominal)	GPA610-8-4L-S6-DRDM-UNV-1/840	6095	50.9	119.9 lm/W	-20°C / 35°C (-4°F / 95°F)	4-F32T8, 2-F54T5HO	*

Normal Ambient Temp High Efficacy	4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
	2000 Lumens (Nominal)	GPA610-2HE-4L-S6-DRDM-UNV-1/840	1656	13.5	122.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1-F32T8	*
	4000 Lumens (Nominal)	GPA610-4HE-4L-S6-DRDM-UNV-1/840	2944	23.5	125.5 lm/W	-20°C / 35°C (-4°F / 95°F)	2-F32T8, 1-F54T5HO	*
	6000 Lumens (Nominal)	GPA610-6HE-4L-S6-DRDM-UNV-1/840	4733	38.4	123.3 lm/W	-20°C / 35°C (-4°F / 95°F)	3-F32T8	*

NOTE:
System data as of 11/01/23.
Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300 10141 Olney Street
 F: 626-454-8399 El Monte, CA 91731
www.lalighting.com Made in the USA




Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 02/05/24



PHOTOMETRIC DATA



GPA610-4-4L-S6-DRDM-UNV-1/840
TEST NO. = LA-T3925b
NO. OF LED ROWS = 1
SYSTEM WATT (W) = 26.7
CRI ≥ 80
L70(Hrs.) ≥ 50,000
PHOTOMETRY TYPE = C

ZONAL LUMEN SUMMARY			
DEGREES	LUMENS	% LAMP	% FIXTURE
0-30	961	24	32
0-40	1563	38	52
0-60	2745	67	91
0-90	2989	73	99
90-120	5	0	0
90-150	15	0	0
90-180	18	0	1
0-180	3007	74	100.0

SPACING CRITERION	
ALONG	ACROSS
1.13	1.23

Luminaire Output = 3007 lumens
 Luminaire Efficacy = 112.6 lm/W
 Luminaire Efficiency = 73.6%



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com
 10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 02/05/24

